

Disclaimer: Disclaimer: This installation guide is intended to clarify the install of your new SOUL exhaust. **Please read this guide in full before beginning installation.** Do take proper precautions and safety measures when working on your vehicle and perform this work at your own risk.



Included:

- o (2) Muffler Bypass Pipes

Packing Sign Off _____

Shipped on ____ / ____ / ____



Step 1: With the rear of the vehicle raised and supported safely, locate the 13mm exhaust tip mounting bolts and loosen. Slide the exhaust tips off of the vehicle.



Step 2: Loosen 13mm sliding exhaust clamp bolts.



Step 3: Slide clamps off the mufflers and onto the catalytic converter sections.



Step 4: Remove 10mm bolt from bumper support rod.



Step 5: Remove T30 bolt from other side of the bumper support rod.



Step 6: Remove 3 x 13mm muffler support bracket nuts.



Step 7: Remove the OEM mufflers from the vehicle.



Step 8: Slide the SOUL muffler bypass pipes into the factory clamps and tighten just enough to allow for final adjustment after tips are installed



Step 9: Loosely install factory / SOUL exhaust tips. Line up muffler bypass piping and tips to be suitable for placement in the bumper.



Step 10: Once final fitment is lined up, torque factory clamps and exhaust tip bolts. Enjoy your new muffler bypass pipe!

You have now successfully completed the installation of your new Soul Performance Products exhaust components! Thank you for your business and if you have any questions during/after the installation please do not hesitate to call or email at the details below.

⚠ You may find that after your first full heat cycle of the exhaust that you need to re-adjust the tip placement to your liking. Additionally, the tone and sound of your exhaust will likely change as the mufflers get broken in, roughly a thousand miles or so.

⚠ You may notice smoke and fumes coming from the system upon first starting up the vehicle. This is due to oils used in manufacturing and is not a problem. The smell will dissipate in a short period of time after the exhaust has reached normal operating temperature.

SOUL PERFORMANCE PRODUCTS

2300 Maryland Road | Suite B
Willow Grove, PA 19090
(267) 818-3201 | Office
customerservice@soulpp.com

SOUL
PERFORMANCE PRODUCTS